

INSTRUCTIONS: This notice shall be completed and submitted by persons proposing to construct projects permitted under the "General Permit for Construction of Water Main Extensions for Public Water Systems" in Rule 62-555.405, F.A.C. AT LEAST 30 DAYS BEFORE BEGINNING CONSTRUCTION OF A WATER MAIN EXTENSION PROJECT, complete and submit one copy of this notice to the appropriate Department of Environmental Protection (DEP) District Office or Approved County Health Department (ACHD) along with payment of the proper permit processing fee. (When completed, Part II of this notice serves as the preliminary design report for a water main extension project, and thus, it is unnecessary to submit a separate preliminary design report or drawings, specifications, and design data with this notice.) All information provided in this notice shall be typed or printed in ink. The DEP permit processing fee for projects requiring the services of a professional engineer during design is \$650, and the DEP permit processing fee for projects not requiring the services of a professional engineer during design is \$500.\* Some ACHDs charge a county permit processing fee in addition to the DEP permit processing fee. Checks for permit processing fees shall be made payable to the Department of Environmental Protection or the appropriate ACHD. NOTE THAT A SEPARATE NOTIFICATION AND A SEPARATE PERMIT PROCESSING FEE ARE REQUIRED FOR EACH NON-CONTIGUOUS PROJECT.

I.	<b>General Project Information</b>		
A.	Name of Project:		
B.	Description of Project and Its Purpose:		
C.	Location of Project		
	County Where Project Located:		
	2. Description of Project Location:		
	Estimate of Cost to Construct Project:		
E.	Estimate of Dates for Starting and Completing Construction of Project:		
F.	Permittee		
	PWS/Company Name:	PWS Identification No.:*	
	PWS Type:* Community Non-Transient Non-Community	☐ Transient Non-Community ☐ Consecutive	
	Contact Person:	Contact Person's Title:	
	Contact Person's Mailing Address:		
	City:	State: Zip Code:	
	Contact Person's Telephone Number:	Contact Person's Fax Number:	
	Contact Person's E-Mail Address:		
* This information is required only if the permittee is a public water system (PWS).			
G.	Public Water System (PWS) Supplying Water to Project		
	PWS Name: Pace Water System, Inc.	PWS Identification No.: 1570671	
	PWS Type:	☐ Transient Non-Community ☐ Consecutive	
	PWS Owner: Pace Water System, Inc.		
	Contact Person: Rachel Lee, P.E.	Contact Person's Title: Utility Engineer	
	Contact Person's Mailing Address: 4401 Woodbine Rd.		
	City: Pace	State: Fl Zip Code: 32571	
	Contact Person's Telephone Number: 850.994.5129	Contact Person's Fax Number: 850.994.6920	
	Contact Person's E-Mail Address: rlee@pacewater.org		

<sup>\*</sup> Except as noted in paragraphs 62-555.520(3)(a) and (b), F.A.C., projects shall be designed under the responsible charge of one or more professional engineers licensed in Florida.

<sup>&</sup>lt;sup>†</sup> Non-contiguous projects are projects that are neither interconnected nor located nearby one another (i.e., on the same site, on adjacent streets, or in the same neighborhood).

Project Name: Permittee:						
H. Public Water System (PWS) that Will Own Project After It Is Placed into Permanent Operation						
_	PWS Name: Pace Water System, Inc.	J		PWS Identification No	o.:* 1570671	
_	•	n-Transient Non-Com		ent Non-Community	Consecutive	
	PWS Owner: Pace Water System, Inc.	II Transient I ton Com		ent i ton community	Consecutive	
_	Contact Person: Rachel Lee, P.E.		Contact Pe	erson's Title: Utility E	ngineer	
_	Contact Person's Mailing Address: 4401 We	oodhine Rd				
	City: Pace	bodome Rd.	State: Fl	7in Co	ode: 32571	
	Contact Person's Telephone Number: 850.9	04 5120		erson's Fax Number: 8		
	Contact Person's E-Mail Address: rlee@pac		Contact 1	ASON S T'AX INUMBEL. 6	30.994.0920	
			sting DWC			
* This information is required only if the owner/operator is an existing PWS.  I. Professional Engineer(s) or Other Person(s) in Responsible Charge of Designing Project*						
_		ili Kespolisible Charge	of Designing Frojec	ι·		
	Company Name:		T:41-(a) af	Danieran(s).		
	Designer(s):		Title(s) of	Designer(s):		
(	Qualifications of Designer(s):		<u> </u>			
	Professional Engineer(s) Licensed in Flo	orida – License Numbe	er(s):			
أا	Public Officer(s) Employed by State, Co			nit of State <sup>†</sup>		
i l	Plumbing Contractor(s) Licensed in Flor					
Fi	Mailing Address of Designer(s):				_	
_	City:		State:	Zip Co	nde.	
_	Telephone Number of Designer(s):			er of Designer(s):	ouc.	
	E-Mail Address(es) of Designer(s):		1 ax I vallic	ci oi Designer(s).		
'	E-Man Address(es) of Designer(s).					
*	Except as noted in paragraphs 62-555.520	$\frac{O(3)(a)}{O(3)(a)}$ and $\frac{O(3)(b)}{O(3)(a)}$	projects shall be de	sianad undar the respe	onsible charge of one	
	or more professional engineers licensed in		, projecis shan be de	signeu unuer ine respo	msibile charge of one	
†	Attach a detailed construction cost estima		at to construct this mu	ainatia \$10,000 am laa		
^						
, ,	Attach documentation showing that this pr					
	documentation showing that this project in					
	units, and a detailed construction cost esti	mate snowing that the	cost to construct this	s project is \$50,000 or	tess.	
II.	Preliminary Design Report for Project*					
	ervice Area, Water Use, and Service Pressu	re Information				
	. Design Type and Number of Service Con		Daily Water Deman	ds and Maximum-Dav	Water Demands, in	
	the Entire Area to Be Served by the Water				,	
			acted chack and the	D = Total Average		
			C = Average Daily	Daily Water Demanda,		
			Water Demand Per		E = Total Maximum-	
		B = Number of Service	Service Connection,	Residential Service	Day Water Demand <sup>b</sup> ,	
	A = Type of Service Connection	Connections	gpd	Connections)	gpd	
	Single-Family Home			0		
	Mobile Home			0		
	Apartment			0		
a. Description of Commercial, Institutional, or Industrial Facilities and Explanation of Method(s) Used to Estimate Average						
	Commercial, Institutional, or Industrial Facility <sup>a</sup> Total  a Description of Commercial Institution	0 nal_or_Industrial_Facil	ities and Explanation	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institution	nal, or Industrial Facil	-	of Method(s) Used to	Estimate Average	
	Total	nal, or Industrial Facil	ities and Explanation	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institution	nal, or Industrial Facil	-	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institution	nal, or Industrial Facil	-	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institution	nal, or Industrial Facil	-	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institutio Daily Water Demand for These Facili	nal, or Industrial Facil ties:	•	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institution	nal, or Industrial Facil ties:	•	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institutio Daily Water Demand for These Facili	nal, or Industrial Facil ties:	•	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institutio Daily Water Demand for These Facili	nal, or Industrial Facil ties:	-	of Method(s) Used to	Estimate Average	
	Total  a. Description of Commercial, Institutio Daily Water Demand for These Facili	nal, or Industrial Facil ties:	-	of Method(s) Used to	Estimate Average	

		EXTENSIONS TOWN WOO
Pro	oject Nam	e: Permittee:
2	System	ation of Peaking Factor(s) or Method(s) Used to Estimate Design Peak-Hour Water Demand and, for Small Water as that Use Hydropneumatic Tanks or that Are Not Designed to Provide Fire Protection, Peak Instantaneous Water d:
3	B. Design	Fire-Flow Rate and Duration:
		Service Pressure Range:
1	. ATTA WATE OFFS I SUPPL	The Information  CH A SITE PLAN OR SKETCH SHOWING THE SIZE AND APPROXIMATE LOCATION OF NEW OR ALTERED OF MAINS, SHOWING THE APPROXIMATE LOCATION OF HYDRANTS, VALVES, METERS, AND BLOWING SAID MAINS, AND SHOWING HOW SAID MAINS CONNECT TO THE PUBLIC WATER SYSTEM OF ANY OF THE PROJECT.
2		otion of Any Areas Where New or Altered Water Mains Will Cross Above or Under Surface Water or Be Located in at Is Known to Be Aggressive:
	Son th	at is Known to be rigglessive.
	allowe	ng requirements do not apply to this project or if this project includes exceptions to any of the following requirements as d by rule, mark "X" before the requirements and complete Part II.C.2 below. RSWW = Recommended Standards for Works as incorporated into Rule 62-555.330, F.A.C.  a. This project is being designed to keep existing water mains and service lines in operation during construction or to minimize interruption of water service during construction. [RSWW 1.3.a; exceptions allowed under FAC 62-555.330]  b. All pipe, pipe fittings, pipe joint packing and jointing materials, valves, fire hydrants, and meters installed under this project will conform to applicable American Water Works Association (AWWA) standards. [FAC 62-555.320(21)(b), RSWW 8.0, and AWWA standards as incorporated into FAC 62-555.330; exceptions allowed under FAC 62-555.320(21)(c)]  c. All public water system components, excluding fire hydrants, that will be installed under this project and that will come into contact with drinking water will conform to NSF International Standard 61 as adopted in Rule 62-555.320(3)(b), F.A.C., or other applicable standards, regulations, or requirements referenced in paragraph 62-555.320(3)(b), F.A.C. [FAC 62-555.320(3)(b); exceptions allowed under FAC 62-555.320(3)(d)]  d. All pipe and pipe fittings installed under this project will contain no more than 8.0% lead, and any solder or flux used in this project will contain no more than 0.2% lead. [FAC 62-555.320]  e. All pipe and pipe fittings installed under this project will be color coded or marked in accordance with subparagraph 62-555.320(21)(b)3, F.A.C., using blue as a predominant color. (Underground plastic pipe will be solid-wall blue pipe, will have a co-extruded blue external skin, or will be white or black pipe with blue stripes incorporated into, or applied to, the pipe wall; and underground metal or concrete pipe will have blue stripes incorporated into, or applied to, the pipe wall; and underground metal or concrete pipe will have blue stri
		f. All new or altered water mains included in this project are sized after a hydraulic analysis based on flow demands and pressure requirements. ATTACH A HYDRAULIC ANALYSIS JUSTIFYING THE SIZE OF ANY NEW OR ALTERED WATER MAINS WITH AN INSIDE DIAMETER OF LESS THAN THREE INCHES. [FAC 62-555.320(21)(b) and RSWW 8.1]

Project Name:		Permittee:
1 Toject Ivanic.		
	g.	The inside diameter of new or altered water mains that are included in this project and that are being designed
		to provide fire protection and serve fire hydrants will be at least six inches. [FAC 62-555.320(21)(b) and RSWW 8.1.2]
<del></del>	h.	New or altered water mains that are included in this project and that are <u>not</u> being designed to carry fire flows
		do <u>not</u> have fire hydrants connected to them. [FAC 62-555.320(21)(b) and RSWW 8.1.5]
	i.	This project is being designed to minimize dead-end water mains by making appropriate tie-ins where
		practical. [FAC 62-555.320(21)(b) and RSWW 8.1.6.a]
	j.	New or altered dead-end water mains included in this project will be provided with a fire or flushing hydrant or
		blow-off for flushing purposes. [FAC 62-555.320(21)(b) and RSWW 8.1.6.b]
	k.	Sufficient valves will be provided on new or altered water mains included in this project so that inconvenience
		and sanitary hazards will be minimized during repairs. [FAC 62-555.320(21)(b) and RSWW 8.2]
	1.	New or altered fire hydrant leads included in this project will have an inside diameter of at least six inches and
		will include an auxiliary valve. [FAC 62-555.320(21)(b) and RSWW 8.3.3]
	m.	
		be located at least three feet from any existing or proposed storm sewer, stormwater force main, pipeline
		conveying reclaimed water regulated under Part III of Chapter 62-610, F.A.C., or vacuum-type sanitary sewer;
		at least six feet from any existing or proposed gravity- or pressure-type sanitary sewer, wastewater force main,
		or pipeline conveying reclaimed water not regulated under Part III of Chapter 62-10, F.A.C.; and at least ten
		feet from any existing or proposed "on-site sewage treatment and disposal system." [FAC 62-555.314(4)]
	n.	At high points where air can accumulate in new or altered water mains included in this project, provisions will
		be made to remove the air by means of air relief valves, and automatic air relief valves will <u>not</u> be used in
		situations where flooding of the valve manhole or chamber may occur. [FAC 62-555.320(21)(b) and RSWW 8.4.1]
	0.	The open end of the air relief pipe from all automatic air relief valves installed under this project will be
		extended to at least one foot above grade and will be provided with a screened, downward-facing elbow. [FAC
		62-555.320(21)(b) and <i>RSWW</i> 8.4.2]
	p.	New or altered chambers, pits, or manholes that contain valves, blow-offs, meters, or other such water
		distribution system appurtenances and that are included in this project will <u>not</u> be connected directly to any
		sanitary or storm sewer, and blow-offs or air relief valves installed under this project will <u>not</u> be connected
		directly to any sanitary or storm sewer. [FAC 62-555.320(21)(b) and RSWW 8.4.3]
	q.	New or altered water mains included in this project will be installed in accordance with applicable AWWA
		standards or in accordance with manufacturers' recommended procedures. [FAC 62-555.320(21)(b), RSWW 8.5.1, and
	r.	AWWA standards as incorporated into FAC 62-555.330] A continuous and uniform bedding will be provided in trenches for underground pipe installed under this
	1.	project; backfill material will be tamped in layers around underground pipe installed under this project and to a
		sufficient height above the pipe to adequately support and protect the pipe; and unsuitably sized stones (as
		described in applicable AWWA standards or manufacturers' recommended installation procedures) found in
		trenches will be removed for a depth of at least six inches below the bottom of underground pipe installed
		under this project. [FAC 62-555.320(21)(b), RSWW 8.5.2]
	s.	All water main tees, bends, plugs, and hydrants installed under this project will be provided with thrust blocks
	٥.	or restrained joints to prevent movement. [FAC 62-555.320(21)(b) and RSWW 8.5.4]
	t.	New or altered water mains that are included in this project and that will be constructed of asbestos-cement or
	٠.	polyvinyl chloride pipe will be pressure and leakage tested in accordance with AWWA Standard C603 or
		C605, respectively, as incorporated into Rule 62-555.330, F.A.C., and all other new or altered water mains
		included in this project will be pressure and leakage tested in accordance with AWWA Standard C600 as
		incorporated into Rule 62-555.330. [FAC 62-555.320(21)(b)1 and AWWA standards as incorporated into FAC 62-555.330]
	u.	New or altered water mains, including fire hydrant leads and including service lines that will be under the
	u.	control of a public water system and that have an inside diameter of three inches or greater, will be disinfected
		and bacteriologically evaluated in accordance with Rule 62-555.340, F.A.C. [FAC 62-555.320(21)(b)2 and FAC 62-
		555.340]
<u></u>	v.	New or altered water mains that are included in this project and that will be installed in areas where there are
<del></del>		known aggressive soil conditions will be protected through use of corrosion-resistant water main materials,
		through encasement of the water mains in polyethylene, or through provision of cathodic protection. [FAC 62-
		555.320(21)(b) and RSWW 8.5.7.d]

Project Name:		Permittee:
	w.	New or relocated, underground water mains included in this project will be laid to provide a horizontal distance of at least three feet between the outside of the water main and the outside of any existing or proposed vacuum-
		type sanitary sewer, storm sewer, stormwater force main, or pipeline conveying reclaimed water regulated under Part III of Chapter 62-610, F.A.C.; a horizontal distance of at least six feet between the outside of the
		water main and the outside of any existing or proposed gravity-type sanitary sewer (or a horizontal distance of
		at least three feet between the outside of the water main and the outside of any existing or proposed gravity-
		type sanitary sewer <u>if the bottom of the water main will be laid at least six inches above the top of the sewer</u> ); a horizontal distance of at least six feet between the outside of the water main and the outside of any existing or
		proposed pressure-type sanitary sewer, wastewater force main, or pipeline conveying reclaimed water not
		regulated under Part III of Chapter 62-610, F.A.C.; and a horizontal distance of at least ten feet between the
		outside of the water main and all parts of any existing or proposed "on-site sewage treatment and disposal
	х.	system." [FAC 62-555.314(1); exceptions allowed under FAC 62-555.314(5)]  New or relocated, underground water mains that are included in this project and that will cross any existing or
	Λ.	proposed gravity- or vacuum-type sanitary sewer or storm sewer will be laid so the outside of the water main is at least six inches above the other pipeline or at least 12 inches below the other pipeline; and new or relocated,
		underground water mains that are included in this project and that will cross any existing or proposed pressure-
		type sanitary sewer, wastewater or stormwater force main, or pipeline conveying reclaimed water will be laid
		so the outside of the water main is at least 12 inches above or below the other pipeline. [FAC 62-555.314(2);
	у.	exceptions allowed under FAC 62-555.314(5)] At the utility crossings described in Part II.C.1.w above, one full length of water main pipe will be centered
	<i>J</i> -	above or below the other pipeline so the water main joints will be as far as possible from the other pipeline or
		the pipes will be arranged so that all water main joints are at least three feet from all joints in vacuum-type
		sanitary sewers, storm sewers, stormwater force mains, or pipelines conveying reclaimed water regulated under
		Part III of Chapter 62-610, F.A.C., and at least six feet from all joints in gravity- or pressure-type sanitary
		sewers, wastewater force mains, or pipelines conveying reclaimed water <u>not</u> regulated under Part III of Chapter 62-610, F.A.C. [FAC 62-555.314(2); exceptions allowed under FAC 62-555.314(5)]
	z.	New or altered water mains that are included in this project and that will cross above surface water will be
		adequately supported and anchored, protected from damage and freezing, and accessible for repair or
		replacement. [FAC 62-555.320(21)(b) and RSWW 8.7.1]
	aa.	New or altered water mains that are included in this project and that will cross under surface water will have a minimum cover of two feet. [FAC 62-555.320(21)(b) and RSWW 8.7.2]
	bb.	New or altered water mains that are included in this project and that will cross under surface water courses
		greater than 15 feet in width will have flexible or restrained, watertight pipe joints and will include valves at
		both ends of the water crossing so the underwater main can be isolated for testing and repair; the
		aforementioned isolation valves will be easily accessible and will <u>not</u> be subject to flooding; the isolation valve
		closest to the water supply source will be in a manhole; and permanent taps will be provided on each side of the
		isolation valve within the manhole to allow for insertion of a small meter to determine leakage from the underwater main and to allow for sampling of water from the underwater main. [FAC 62-555.320(21)(b) and RSWW
		8.7.2]
	cc.	This project is being designed to include proper backflow protection at those new or altered service
		connections where backflow protection is required or recommended under Rule 62-555.360, F.A.C., or in
		Recommended Practice for Backflow Prevention and Cross-Connection Control, AWWA Manual M14, as incorporated into Rule 62-555.330, F.A.C.; or the public water system that will own this project after it is
		placed into operation has a cross-connection control program requiring water customers to install proper
		backflow protection at those service connections where backflow protection is required or recommended under
		Rule 62-555.360, F.A.C., or in AWWA Manual M14. [FAC 62-555.360 and AWWA Manual M14 as incorporated into
	.1.1	FAC 62-555.330]
	dd.	Neither steam condensate, cooling water from engine jackets, nor water used in conjunction with heat exchangers will be returned to the new or altered water mains included in this project. [FAC 62-555.320(21)(b) and
		RSWW 8.8.2]

	10 1 OK 1 1103
Project Name:	Permittee:
<ol><li>Explanation for Requirements Marked "X" in Part II.C.1 A Alternatives as Required by Rule for Exceptions to Require</li></ol>	bove, Including Justification, Documentation, Assurances, and/or ements in Part II.C.1:
I completed Part II of this notice, and the information provided in	Part II and on the attachment(s) to Part II is true and accurate to the
best of my knowledge and belief.	Tart II and on the attachment(s) to I art II is true and accurate to the
Signature, Seal, and Date of Professional Engineer (PE) or	Signature, Seal, and Date of Professional Engineer (PE) or
Signature and Date of Other Person in Responsible Charge of	Signature and Date of Other Person in Responsible Charge of
Designing Project:*	Designing Project:*
District the state of the state	
Printed/Typed Name:	Printed/Typed Name:
License Number of PE or License Number or Title of Other	License Number of PE or License Number or Title of Other
Person in Responsible Charge of Designing Project:*	Person in Responsible Charge of Designing Project:*
Dortion of Draliminary Design Deposit for Which Design '11	Dortion of Draliminary Design Deposit for Which Designation
Portion of Preliminary Design Report for Which Responsible:	Portion of Preliminary Design Report for Which Responsible:

<sup>\*</sup> Except as noted in paragraphs 62-555.520(3)(a) and (b), F.A.C., projects shall be designed under the responsible charge of one or more PEs licensed in Florida. If this project is being designed under the responsible charge of one or more PEs licensed in Florida, Part II of this notice shall be completed, signed, sealed, and dated by the PE(s) in responsible charge. If this project is not being designed under the responsible charge of one or more PEs licensed in Florida, Part II shall be completed, signed, and dated by the person(s) in responsible charge of designing this project.

EXT	ENSIONS FOR PWSs		
Project Name:	Permittee:		
III. Certifications			
A. Certification by Permittee			
I am duly authorized to sign this notice on behalf of my knowledge and belief, this project complies with begun yet and that, to the best of my knowledge and • construction of water mains conveying raw or processing to expect the construction of drinking water treatment, pumprocessing to expect the construction of an interconnection between present a "new system" as described under subsection of expectation of water mains that will remain dry (A specific construction permit is required for each	n Chapter 62-555, F.A.C. I also cert belief, this project does <u>not</u> include partially treated drinking water; ing, or storage facilities or conflict nated by low-molecular-weight petrole viously separate public water system 52-555.525(1), F.A.C.; or y following completion of constructions	ify that construction of this project has <u>not</u> any of the following construction work:  nanholes; um products or organic solvents; as or construction of water mains that create on.	
I understand that, if this project is designed under the Florida, the permittee must retain a Florida-licensed purpose of determining in general if the construction construction permit, including the approved prelimic complete record drawings prepared for this project. completion to the Department and obtain written approject into operation for any purpose other than distributions.	PE to take responsible charge of ins in proceeds in compliance with the D nary design report, for this project.  I also understand that the permittee proval, or clearance, from the Depar	specting construction of this project for the epartment of Environmental Protection I understand that the permittee must have must submit a certification of construction	
Signature and Date	Printed or Typed Name	Title	
B. Certification by PWS Supplying Water to Project			
I am duly authorized to sign this notice on behalf of the PWS identified in Part I.G of this notice. I certify that said PWS will supply the water necessary to meet the design water demands for this project. As indicated below, the water treatment plant(s) which this project will be connected has(have) the capacity necessary to meet the design water demands for this project, and certify that all other PWS components affected by this project also have the capacity necessary to meet the design water demands for this project. I certify that said PWS is in compliance with applicable planning requirements in Rule 62-555.348, F.A.C.; applicable cross-connection control requirements in Rule 62-555.360, F.A.C.; and to the best of my knowledge and belief, all applicable rules in Chapters 62-550, 62-555, and 62-699, F.A.C.; furthermore, I certify that, to the best of my knowledge and belief, said PWS's connection to this project will not cause said PWS to be in noncompliance with Chapter 62-550 or 62-555 F.A.C. I also certify that said PWS has reviewed the preliminary design report for this project and that said PWS considers the connection(s) between this project and said PWS acceptable as designed.  • Name(s) of Water Treatment Plant(s) to Which this Project Will Be Connected: Pace Water System, Inc.			
<ul> <li>Total Permitted Maximum Day Operating Capa</li> <li>Total Maximum Day Flow at Plant(s) as Record</li> </ul>		During Past 12 Months, gpd: <u>7,330,000</u>	
	Rachel Lee, P.E.	Utility Engineer	
Signature and Date	Printed or Typed Name	Title	
C. Certification by PWS that Will Own Project After In	<b>3.</b>		
I am duly authorized to sign this notice on behalf of this project after it is placed into permanent operation this project and that said PWS considers this project	the PWS identified in Part I.H of thon. I also certify that said PWS has r	is notice. I certify that said PWS will own	
	Rachel Lee, P.E.	Utility Engineer	
Signature and Date	Printed or Typed Name	Title	

Project Name:	Permittee:
---------------	------------

D. Certification by Professional Engineer(s) in Responsible Charge of Designing Project\*

I, the undersigned professional engineer licensed in Florida, am in responsible charge of designing this project. I certify that, to the best of my knowledge and belief, the design of this project complies with Chapter 62-555, F.A.C. I also certify that, to the best of my knowledge and belief, this project is not being designed to include any of the following construction work:

- construction of water mains conveying raw or partially treated drinking water;
- construction of drinking water treatment, pumping, or storage facilities or conflict manholes;
- construction of water mains in areas contaminated by low-molecular-weight petroleum products or organic solvents;

(A specific construction permit is required for each project involving any of the above listed construction work)

- construction of an interconnection between previously separate public water systems or construction of water mains that create a "new system" as described under subsection 62-555.525(1), F.A.C.; or
- construction of water mains that will remain dry following completion of construction.

(A specific construction permit is required for each project involved	any of the above listed construction work.)
Signature, Seal, and Date:	Signature, Seal, and Date:
Deints 4/Tons 4 Nones	Daints d/Tamed Names
Printed/Typed Name:	Printed/Typed Name:
License Number:	License Number:
Portion of Preliminary Design Report for Which Responsible:	Portion of Preliminary Design Report for Which Responsible:

<sup>\*</sup> Except as noted in paragraphs 62-555.520(3)(a) and (b), F.A.C., projects shall be designed under the responsible charge of one or more professional engineers (PEs) licensed in Florida. If this project is being designed under the responsible charge of one or more PEs licensed in Florida, Part III.D of this notice shall be completed by the PE(s) in responsible charge. If this project is not being designed under the responsible charge of one or more PEs licensed in Florida, Part III.D does not have to be completed.